



Couplings offer installation flexibility for at-grade or wall-mounted applications. Couplings can be used to improve light output by raising fixtures above grade, clearing obstructions, and achieving new angles and positions. In addition, the T-Mount can be used with only one riser to reduce costs, labor, and parts.

Couplings



STRAIGHT



90-DEGREE



T-MOUNT



Couplings

	STRAIGHT*	90-DEGREE	T-MOUNT
NO RISER	COUP-XX	ELBW-050-XX	TMNT-050-XX
6" RISER	6R-XX	6R-90-XX	6R-T-XX
8" RISER	8R-XX	8R-90-XX	8R-T-XX
12" RISER	12R-XX	12R-90-XX	12R-T-XX
18" RISER	18R-XX	18R-90-XX	18R-T-XX
24" RISER	24R-XX	24R-90-XX	24R-T-XX
30" RISER	30R-XX	30R-90-XX	30R-T-XX
36" RISER	36R-XX	36R-90-XX	36R-T-XX

* Remove hyphens when ordering.
 † XX Indicates powder coat color code.



JB WITH STRAIGHT



JB WITH 90-DEGREE



JB WITH T-MOUNT



NP WITH STRAIGHT



NP WITH 90-DEGREE



NP WITH T-MOUNT