FXLuminaire.


LED Path Lights



The EA produces a soft, efficient LED glow, and was created specifically for those looking for sharp, tight geometric angles. Its sleek look and FX-strong construction make it the perfect choice for many different types of pathways.

EA: Path Light

NUMBER OF LEDS:	1
HALOGEN LUMEN OUTPUT EQUIVALENT:	10 Watt
USEFUL LED LIFE (L70):	50,000 hrs avg
INPUT VOLTAGE:	10 to 15V
VA TOTAL: (Use this number to size the transformer)	2.4
WATTS USED:	2.0
LUMENS PER WATT (EFFICACY)	19.4
MAX LUMENS:	39
CCT (Ra)	86



ORDERING INFORMATION

EA: Path Light

2

3

4

5

"Beam angle is defined as two times the vertical angle at which the intensity is 50% of the maximum."

Beam angle is calculated using LM-79 method for SSL Luminaires:

 5
 20 fc
 2.5 fc
 0.2 fc
 Moun

 10 fc
 11 fc
 0.1 fc
 Total I

 5 fc
 0.5 fc
 50% Max Candela

 Distance in units of mount height

Mount height: 1ft Total LLF: 1

		OPTIONS (TOP ASSEM	BLIJ: UIUE	11+2			and the second	
Step	Description	Code						AB = Antique Bronze* (On Copper/Brass)
1	TOP ASSEMBLY	EALEDTA					-	AT = Antique Tumbled
2	TOP FINISH	AB*, AT*, CU, NP*, WG, FW,	AL, BZ, DG,	WI, VF, SB, FB				(On Copper/Brass)
EXAM	PLE: EALEDTA-FB	= EA Top Assembly - Flat B	lack Finish					CU = Copper
FACT	ORY INSTALLED	OPTIONS (RISER ASSE	MBLY): Ord	ler 1 + 2 (op	tional) + 3 +	- 4 + 5	1. Sec. 1	
Step	Description	Code						NP = Nickel Plate*
1	RISER TYPE	Р					POWE	DER COAT
2	OPTIONAL ZD	ZD (Refer to the Luxor pag	e in the Light	ing Control see	ction)]
3	LAMP	1LED (50,000 avg. life hou	 rs)				WG = White Gloss	
4	RISER HEIGHT	8RA, 12RA, 18RA, 24RA, 3	6RA (in inche	5)			FW = Flat White	
5	FINISH	AB*, AT*, CU, NP*, WG, FW,	/G, FW, AL, BZ, DG, WI, VF, SB, FB					
	PLE: P-ZD-1LED-1							
FIELD	DINSTALLED OP	TIONS: Order Individua	ally	-				BZ = Bronze Metallic
FIELD	D INSTALLED OP	TIONS: Order Individua	ally	Ø		w	-	BZ = Bronze Metallic DG = Desert Granite
FIELD Moun Long S	D INSTALLED OP	0000) 2.5" x 10" Included >	ally	Ŷ	V	W		DG = Desert Granite
FIELD Moun Long S	D INSTALLED OP Iting Options Slot Spike (25001584	0000) 2.5" x 10" Included	ally	Ÿ	V	Ű		
FIELD Moun Long S Super S	D INSTALLED OP ting Options Slot Spike (25001584 Slot Spike (753900)	0000) 2.5" x 10" Included > 2" x 10" x 12"	ally	Super Slot Spike	Super J-Box XX**	Post Mount XX**		DG = Desert Granite
FIELE Moun Long S Super S Super J Post M	D INSTALLED OP ting Options Slot Spike (25001584 Slot Spike (753900) . I-Box (SJ-XX**) 2.5" >	0000) 2.5" x 10" Included > 2" x 10" x 12" x 13"	Long					DG = Desert Granite WI = Weathered Iron
FIELC Moun Long S Super 3 Super J Post M EXAM	D INSTALLED OP ting Options Filot Spike (25001584 Slot Spike (753900) . I-Box (SJ-XX**) 2.5" × Nount (PM-XX**) 2.5"	0000) 2.5" x 10" Included > 2" x 10" x 12" x 13"	Long					DG = Desert Granite WI = Weathered Iron VF = Verde Speckle
FIELC Moun Long S Super 3 Super J Post M EXAM	D INSTALLED OP Iting Options Slot Spike (25001584 Slot Spike (753900) 2 I-Box (SJ-XX**) 2.5" Nount (PM-XX**) 2.5" IPLE: 753900 = Sup	0000) 2.5" x 10" Included > 2" x 10" x 12" x 13" per Slot Spike EA 1LED ISOF	Long	Slot Spike				DG = Desert Granite WI = Weathered Iron VF = Verde Speckle



All EA path lights com standard with amber, green, blue and frosted filters

Note: Only the copper portions of the path lights are powder coated. The brass pieces remain natural.

* May require longer lead time ** Denotes finish code

LED

FXLuminaire.