



DETAIL LEGEND:

- ① FX LUMINAIRE "PD" FIXTURE PER PLAN
- ② DIRECT BURY UF/UL, COPPER, LOW VOLTAGE CABLE WITH UL 486D (IEC/ EN 60998) RATED WATERPROOF CONNECTION. COIL 12" SERVICE LOOP IN CONSTRUCTION SLEEVE.
- ③ SITE BUILT BOLLARD
- ④ CONCRETE FOOTING
- ⑤ ELECTRICAL CONDUIT PER LOCAL CODE
- ⑥ 12 GA MAIN LINE CABLE US
- ⑦ FINISH GRADE

NOTES

- A. INSTALL TO A UL 1838 (IEC/EN 61437) LISTED TRANSFORMER
- B. FIXTURE REQUIRES 10-15V AC/DC
- C. FIXTURE IS DESIGNED FOR DOWN LIGHTING ONLY. DO NOT USE IN UP LIGHT POSITION
- D. FOR COPPER OR BRASS FIXTURES, AVOID PREMATURE PATINA BY HANDLING WITH GLOVES
- E. FOR LUXOR CONTROL, ASSIGN FIXTURE OR LUXOR CUBE® TO GROUP NUMBER PRIOR TO INSTALLATION



LED WALL LIGHT (PD) BOLLARD MOUNT

FXLuminaire. W.PD.01

NOT TO SCALE
REV: 2020-07-09