



8165 E Kaiser Blvd. Anaheim, CA 92808
www.lightlaboratory.com

Report No: L022211201



Report No: L022211201

Issue Date: 2/23/2022

Report Prepared For: FX Luminaire / Lumascape
1940 Diamond Street, San Marcos, CA, 92078

Model Number: LC-3LED-FW / dFRS11a-3LED-WT

Test: Photometric/Colorimetric/Electrical Test

Standards Used: Appropriate part or all test guidelines were used for test performed:

IESNA LM79: 2019 Approved Methods for Electrical and Photometric Measurements of Solid-State Lighting Products

ANSI NEMA ANSLG C78.377: 2017 Specification of the Chromaticity of Solid State Lighting Products

ANSI C82.77-10:2014: Harmonic Emission Limits-Related Quality Requirements for Lighting Equipment

Description of Sample: Client submitted the sample. Received in working and undamaged condition. No modifications were necessary.

Special Test Condition: Fixture is tested with no special conditions.

Date of Tests: 2/21/22

Seasoning of Sample: No seasoning was performed in accordance with IESNA LM-79.

Equipment List

Equipment Used	Model No	Stock No	Calibration Due Date
Chroma Programmable AC Source	61604	PS-AC02	--
Yokogawa Digital Power Meter	WT210	MT-EL06-S4	4/7/23
HP Power Supply	6032A	PS-DC05-S2	--
Fluke Digital Thermometer	52K/J	MT-TP05	3/17/23
LLI Type C Goniophotometer System	RMG-C-MKII	CD-LL04-GC	--
LLI 2M Sphere	2MR97	CD-SN03-S2	--
LLI Spectroradiometer	SPR-3000	MT-SC01-S2	Before Use

General Information

Manufacturer:	FX Luminaire / Lumascape
Model Number:	LC-3LED-FW / dFRS11a-3LED-WT
Driver Model Number:	N/A

Test Summary

Total Lumens:	305.00
Efficacy:	77.29
Color Redering Index:	83.5
Correlated Color Temperature:	2649
Input Voltage (VDC):	12.00
Input Current (Amp):	0.3603
Input Power (W):	3.95
Input Power Factor:	0.9125
Current ATHD (%):	39.6%

Test Condition

Ambient Temperature (°C):	25.0
Stabilization Time (Hours):	0:35
Total Operating Time (Hours):	1:00





FIG. 1 LUMINAIRE

Colorimetry Test Results




CRI & CCT

x	0.4694
y	0.4208
u'	0.2640
v'	0.5326
CRI	83.50
CCT	2649
Duv	0.00296

R Values

R1	81.31
R2	90.36
R3	98.09
R4	83.83
R5	82.42
R6	90.95
R7	83.20
R8	58.17
R9	8.06
R10	79.54
R11	84.95
R12	79.19
R13	83.14
R14	99.42
R15	72.25





8165 E Kaiser Blvd. Anaheim, CA 92808
www.lightlaboratory.com

Report No: L022211201



Test Methods

Photometric Measurements - Goniophotometer

A Custom Light Laboratory Type C Rotating Mirror Goniophotometer was used to measure candelas(intensity) at each angle of distribution as defined by IESNA for the appropriate fixture type.

Ambient temperature is set to 25°C and is measured from the center of the fixture, within 1ft from the outside of the fixture. Temperature is maintained at 25°C throughout the testing process and the sample is stabilized for at least 30mins and longer as necessary for the sample to achieve stabilization.

Electrical measurements are measured using the listed equipment.

Spectral Measurements - Integrating Sphere

A Sensing Spectroradiometer SPR-3000, in conjunction with Light Laboratory 2 meter integrating sphere was used to measure chromaticity coordinates, correlated color temperature(CCT) and the color rendering index(CRI) for each sample.

Ambient temperature is set to 25°C and is measured from the center of the fixture, within 1ft from the outside of the fixture. Temperature is maintained at 25°C throughout the testing process and the sample is stabilized for at least 30mins and longer as necessary for the sample to achieve stabilization.

Electrical measurements are measured using the listed equipment.

Disclaimers:

The results related only to the samples as received and tested. This report must not be used by the customer to claim product certification, approval or endorsement by NVLAP, NIST or any agency of the Federal Government.

Report Prepared by : Kunjna Modi

Test Report Reviewed by:

Steve Kang
Quality Assurance

**Attached are photometric data reports.*



8165 E. Kaiser Blvd. Anaheim, CA 92808
www.lightlaboratory.com

Photometric Test Report

IES FLOOD REPORT

PHOTOMETRIC FILENAME : L022211201.IES

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] L022211201
[TESTLAB] LIGHT LABORATORY, INC. (www.lightlaboratory.com)
[ISSUEDATE] 2/23/2022
[MANUFAC] FX Luminaire / Lumascape
[LUMCAT] LC-3LED-FW / dFRS11a-3LED-WT
[LUMINAIRE] Lumiled, 3LED, 2700K
[BALLASTCAT] N/A
[OTHER] INDICATING THE CANDELA VALUES ARE ABSOLUTE AND
[MORE] SHOULD NOT BE FACTORED FOR DIFFERENT LAMP RATINGS.
[INPUT] 12VAC
[TEST PROCEDURE] IESNA:LM-79-08

Note: Candela values converted from Type-C to Type-B

CHARACTERISTICS


NEMA Type	7 H x 5 V
Maximum Candela	147
Maximum Candela Angle	-3H -7V
Horizontal Beam Angle (50%)	92.5
Vertical Beam Angle (50%)	85.9
Horizontal Field Angle (10%)	138.2
Vertical Field Angle (10%)	95.5
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Beam Lumens	206
Beam Efficiency	N.A.
Field Lumens	295
Field Efficiency	N.A.
Spill Lumens	9
Luminaire Lumens	305
Total Efficiency	N.A.
Total Luminaire Watts	3.95
Ballast Factor	1.00

IES FLOOD REPORT
PHOTOMETRIC FILENAME : L022211201.IES

AXIAL CANDELA

DEG.	HOR.	DEG.	VERT.
90	1	90	1
85	2	85	1
75	7	75	1
65	19	65	1
55	44	55	6
47.5	69	47.5	15
42.5	83	42.5	28
37.5	96	37.5	51
33	107	33	78
29	116	29	99
25.5	123	25.5	112
22.5	128	22.5	121
19.5	133	19.5	127
17	136	17	131
15	138	15	134
13	140	13	136
11	142	11	139
9	143	9	141
7	144	7	143
5	145	5	144
3	146	3	145
1	146	1	146
0	146	0	146
-1	146	-1	146
-3	146	-3	147
-5	145	-5	147
-7	144	-7	147
-9	143	-9	146
-11	142	-11	146
-13	140	-13	144
-15	138	-15	143
-17	136	-17	142
-19.5	133	-19.5	139
-22.5	128	-22.5	136
-25.5	123	-25.5	131
-29	116	-29	126
-33	107	-33	118
-37.5	96	-37.5	108
-42.5	83	-42.5	96
-47.5	69	-47.5	84
-55	44	-55	67
-65	19	-65	48
-75	7	-75	33
-85	2	-85	19
-90	1	-90	15

AXIAL CANDELA DISPLAY




Maximum Candela = 147 Located At Horizontal Angle =-3, Vertical Angle =-7

H - Horizontal Axial Candela

V - Vertical Axial Candela

ISOCANDELA CURVES



Maximum Candela = 147 Located At Horizontal Angle =-3, Vertical Angle =-7
50% Maximum Candela = 73.5
10% Maximum Candela = 14.7