



8165 E Kaiser Blvd. Anaheim, CA 92808
www.lightlaboratory.com

Report No: L022211212



Report No: L022211212

Issue Date: 2/25/2022

Report Prepared For: FX Luminaire / Lumascape
1940 Diamond Street, San Marcos, CA, 92078

Model Number: NL-6LED-DN-FW-wf / sQAD8-6LED-DN-WF-WT

Test: Photometric/Colorimetric/Electrical Test

Standards Used: Appropriate part or all test guidelines were used for test performed:

IESNA LM79: 2019 Approved Methods for Electrical and Photometric Measurements of Solid-State Lighting Products

ANSI NEMA ANSLG C78.377: 2017 Specification of the Chromaticity of Solid State Lighting Products

ANSI C82.77-10:2014: Harmonic Emission Limits-Related Quality Requirements for Lighting Equipment

Description of Sample: Client submitted the sample. Received in working and undamaged condition. No modifications were necessary.

Special Test Condition: Fixture is tested with no special conditions.

Date of Tests: 2/22/22

Seasoning of Sample: No seasoning was performed in accordance with IESNA LM-79.

Equipment List

Equipment Used	Model No	Stock No	Calibration Due Date
Chroma Programmable AC Source	61604	PS-AC02	--
Yokogawa Digital Power Meter	WT210	MT-EL06-S4	4/7/23
HP Power Supply	6032A	PS-DC05-S2	--
Fluke Digital Thermometer	52K/J	MT-TP05	3/17/23
LLI Type C Goniophotometer System	RMG-C-MKII	CD-LL04-GC	--
LLI 2M Sphere	2MR97	CD-SN03-S2	--
LLI Spectroradiometer	SPR-3000	MT-SC01-S2	Before Use

General Information

Manufacturer:	FX Luminaire / Lumascape
Model Number:	NL-6LED-DN-FW-wf / sQAD8-6LED-DN-WF-WT
Driver Model Number:	N/A

Test Summary

Total Lumens:	641.00
Efficacy:	81.99
Color Redering Index:	83.3
Correlated Color Temperature:	2626
Input Voltage (VDC):	12.00
Input Current (Amp):	0.7809
Input Power (W):	7.82
Input Power Factor:	0.8342
Current ATHD (%):	51.3%

Test Condition

Ambient Temperature (°C):	25.0
Stabilization Time (Hours):	0:35
Total Operating Time (Hours):	1:00





FIG. 1 LUMINAIRE

Colorimetry Test Results




CRI & CCT

x	0.4697
y	0.4184
u'	0.2653
v'	0.5318
CRI	83.30
CCT	2626
Duv	0.00209

R Values

R1	81.34
R2	90.97
R3	97.03
R4	83.27
R5	82.60
R6	91.88
R7	82.30
R8	57.38
R9	7.64
R10	80.98
R11	84.45
R12	80.67
R13	83.39
R14	98.97
R15	72.27



Test Methods

Photometric Measurements - Goniophotometer

A Custom Light Laboratory Type C Rotating Mirror Goniophotometer was used to measure candelas(intensity) at each angle of distribution as defined by IESNA for the appropriate fixture type.

Ambient temperature is set to 25°C and is measured from the center of the fixture, within 1ft from the outside of the fixture. Temperature is maintained at 25°C throughout the testing process and the sample is stabilized for at least 30mins and longer as necessary for the sample to achieve stabilization.

Electrical measurements are measured using the listed equipment.

Spectral Measurements - Integrating Sphere

A Sensing Spectroradiometer SPR-3000, in conjunction with Light Laboratory 2 meter integrating sphere was used to measure chromaticity coordinates, correlated color temperature(CCT) and the color rendering index(CRI) for each sample.

Ambient temperature is set to 25°C and is measured from the center of the fixture, within 1ft from the outside of the fixture. Temperature is maintained at 25°C throughout the testing process and the sample is stabilized for at least 30mins and longer as necessary for the sample to achieve stabilization.

Electrical measurements are measured using the listed equipment.

Disclaimers:

The results related only to the samples as received and tested. This report must not be used by the customer to claim product certification, approval or endorsement by NVLAP, NIST or any agency of the Federal Government.

Report Prepared by : Kunjan Modi

Test Report Reviewed by:



Steve Kang
Quality Assurance

**Attached are photometric data reports.*



8165 E. Kaiser Blvd. Anaheim, CA 92808
www.lightlaboratory.com

Photometric Test Report

IES FLOOD REPORT

PHOTOMETRIC FILENAME : L022211212.IES

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] L022211212
[TESTLAB] LIGHT LABORATORY, INC. (www.lightlaboratory.com)
[ISSUEDATE] 2/23/2022
[MANUFAC] FX Luminaire / Lumascape
[LUMCAT] NL-6LED-DN-FW-wf / sQAD8-6LED-DN-WF-WT
[LUMINAIRE] Lumiled, 6LED, 2700K, Wide Flood (60°)
[BALLASTCAT] N/A
[OTHER] INDICATING THE CANDELA VALUES ARE ABSOLUTE AND
[MORE] SHOULD NOT BE FACTORED FOR DIFFERENT LAMP RATINGS.
[INPUT] 12VAC
[TEST PROCEDURE] IESNA:LM-79-08

Note: Candela values converted from Type-C to Type-B

CHARACTERISTICS


NEMA Type	5 H x 5 V
Maximum Candela	614
Maximum Candela Angle	-1H -17V
Horizontal Beam Angle (50%)	46.8
Vertical Beam Angle (50%)	58.9
Horizontal Field Angle (10%)	91.3
Vertical Field Angle (10%)	98.2
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Beam Lumens	396
Beam Efficiency	N.A.
Field Lumens	570
Field Efficiency	N.A.
Spill Lumens	71
Luminaire Lumens	641
Total Efficiency	N.A.
Total Luminaire Watts	7.82
Ballast Factor	1.00

IES FLOOD REPORT
PHOTOMETRIC FILENAME : L022211212.IES

AXIAL CANDELA

DEG.	HOR.	DEG.	VERT.
90	0	90	0
85	2	85	2
75	8	75	8
65	14	65	15
55	41	55	37
47.5	60	47.5	71
42.5	87	42.5	93
37.5	131	37.5	143
33	201	33	220
29	313	29	340
25.5	434	25.5	456
22.5	522	22.5	536
19.5	585	19.5	588
17	606	17	599
15	600	15	587
13	578	13	560
11	542	11	525
9	511	9	499
7	490	7	481
5	478	5	471
3	470	3	466
1	467	1	464
0	467	0	467
-1	467	-1	469
-3	470	-3	473
-5	478	-5	481
-7	490	-7	495
-9	511	-9	519
-11	542	-11	552
-13	578	-13	590
-15	600	-15	611
-17	606	-17	614
-19.5	585	-19.5	589
-22.5	522	-22.5	520
-25.5	434	-25.5	425
-29	313	-29	300
-33	201	-33	190
-37.5	131	-37.5	119
-42.5	87	-42.5	86
-47.5	60	-47.5	66
-55	41	-55	34
-65	14	-65	14
-75	8	-75	8
-85	2	-85	4
-90	0	-90	0

AXIAL CANDELA DISPLAY




Maximum Candela = 614 Located At Horizontal Angle =-1, Vertical Angle =-17

H - Horizontal Axial Candela

V - Vertical Axial Candela

ISOCANDELA CURVES



Maximum Candela = 614 Located At Horizontal Angle =-1, Vertical Angle =-17
50% Maximum Candela = 307
10% Maximum Candela = 61.4