



DETAIL LEGEND:

- ① FX LUMINAIRE "LL" FIXTURE PER PLAN
- ② STAINLESS STEEL STAND
- ③ BOTTOM OF WATER FEATURE
- ④ WATER LEVEL WITHIN FEATURE
- ⑤ ELECTRICAL CONDUIT WITH SWEEP ELLS, AS REQUIRED
- ⑥ DIRECT BURY, UF/UL, COPPER, LOW VOLTAGE CABLE WITH UL 486D (IEC/EN 60998) RATED WATERPROOF CONNECTION. LEAVE MINIMUM WIRE LOOP COILED FOR FUTURE SERVICE ABOVE WATER LEVEL.

NOTES

- A. FIXTURE REQUIRES 11-15V AC/DC
- B. INSTALL TO A UL 1838 (IEC/EN 61347) LISTED TRANSFORMER
- C. FIXTURE CAN BE USED IN OR OUT OF WATER. NOT FOR SWIMMING POOL USE.
- D. MAX DEPTH IN WATER IS 10 FT (3 M)
- E. FOR LUXOR CONTROL, ASSIGN FIXTURE OR LUXOR CUBE® TO APPROPRIATE GROUP NUMBER PRIOR TO INSTALLATION UNLESS USING LIGHT ASSIGNMENT MODULE (LAM)



DESIGNER SERIES LL LIGHT
FXLuminaire. SP.LL.01

NOT TO SCALE
 REV: 2019-09-05