



PROJECT

CATALOG #

TYPE


NOTES

## CP Wall Light **DESIGNER PREMIUM**

Utilitarian recessed wall light in 1 LED. Available in copper.

### Quick Facts

- Stamped copper construction
- Natural, powder coated, or antiqued copper finish
- Cree® integrated LEDs
- Tamper-resistant features
- Color temperature filters
- Compatible with Luxor® technology
- Phase and PWM dimmable
- Input voltage: 10-15V



# CP Wall Light SPECIFICATIONS

Output	1LED
Total Lumens <sup>†</sup>	10
Input Voltage	10 to 15V
Input Power (W)	2.0
VA	2.4
Efficacy (Lumens/Watt)	5
Color Rendering Index (CRI)	80+
Center Beam Candlepower	6
Dimming	PWM, Phase**
RGBW Available	No
Luxor Compatibility	
Default	Zoning
ZD Option	Zoning/Dimming
Minimum Rated Life (L70)	50,000 Hrs
BUG Rating	B0-U1-G0

<sup>†</sup> Measured using the 3,900K CCT lens. Multipliers for other CCTs include 0.80 (2,700K), 0.65 (4,500K), and 0.65 (5,200K).

\*\* For optimal performance, use a trailing-edge, phase-cut dimmer.

## FX Luminaire

FX Luminaire is an industry-leading manufacturer of landscape and architectural lighting products with a focus on the advancement of LED technology and digital lighting control with zoning, dimming, and color adjustment capabilities. We offer a full spectrum of specification-driven lighting fixtures that can be utilized to create elegant, cutting-edge landscape lighting systems for commercial or residential applications. Our products are available exclusively via our extensive professional distributor network.

## Materials

Stamped C110 copper faceplate, A380 aluminum housing, PBT construction box/sleeve, and stainless steel hardware.

## Wiring

18 AWG (1 mm); SPT-1W; 220°F (105°C); 300V; 10' (3 m) length

## Housing

Die-cast aluminum housing with capacity for one 1LED integrated LEDs.

## Power

Input 10–15 VAC/VDC, 50/60 Hz. Remote transformer required (specify separately).

## Lamp

Integrated module with Cree LEDs. Gold-plated connectors and conformal coated for maximum reliability and corrosion resistance. Proprietary on-board intelligent driver uses firmware-controlled temperature regulation, maximizing LED life. Field upgradeable and replaceable, the LEDs are rated to 50,000 hrs. Maximum drive current: 1 A.

## Socket

Socket contains MoistureBlock™ technology, preventing moisture from wicking up into sealed areas of the fixture.

## Faceplate

Stamped C110 copper faceplate with frosted polycarbonate lens.

## Lens

Polycarbonate lens with shock resistance and high tolerance for thermal expansion and stress.

## Construction Sleeve

Vertical and horizontal ½" (13 mm) NPT knockouts. Sleeve protector included, preventing caving during wall fabrication.

## Optics

Polycarbonate color temperature adjustment lenses included with fixture: 2,700K (pre-installed), 3,900K (no lens), 4,500K and 5,200K options specified separately. Color temperature lenses are field serviceable.

## Finish

Options of natural copper finish, antiqued finish with brushed (Antique Bronze) or tumbled (Antique Tumbled) effect, or TGIC powder coat finish. Antique finishes sealed with a clear TGIC powder coat layer.

## Hardware

Tamper-resistant stainless steel fasteners included.

## Ambient Operating Temperature

0°F to 140°F (-18°C to 60°C)

## Weight

2.3 lbs. (1.0 kg)

## IES Classification

Type IV

## International Compliance

Compliant per IEC 60598-1 and IEC 60598-2-7 when used with International Wall Kit ("EKITWALL").

## Control

ZD option utilizes Luxor technology to zone light fixtures in up to 250 groups, and dim each group in 1% increments between 0 and 100%.

## Sustainability

Innovation meets conservation in the design and manufacturing of our products. Where we can, we use recycled materials while maintaining superior functionality. Our LED products provide high-quality light at optimal energy efficiency, lifespan, and durability.

## Installation Requirements

Designed for recessed installation in a vertical wall in the down lighting position only.

## Warranty

10-year limited warranty














## Manufacturing

9001:2015 ISO certified facility

## Listings



# CP Wall Light ORDERING INFORMATION

Fixture	Luxor Option	Output	Finish
CP*	■ [default] Zone	■ 1LED 10 Lumens	■ CU Natural Copper 
	■ ZD Zone/Dim		■ BZ Bronze Metallic 
			■ DG Desert Granite 
			■ WI Weathered Iron 
			■ SB Sedona Brown 
			■ FB Black 
			■ WG White Gloss 
			■ FW Flat White 
	■ AL Almond 		
			■ SV Silver 
			■ NP Nickel Plate 
			■ AB Antique Bronze 
			■ AT Antique Tumbled 

EXAMPLE FIXTURE CONFIGURATION:  
 CP-ZD-1LED-FB  
 \*Includes Sleeve With Cover (250022040000)




## ACCESSORIES: Specify Separately

Accessories	Code
■ WALL LIGHT CONNECTION KIT 	EKITWALL 

# CP Wall Light PHOTOMETRICS


## CP 1LED Illuminance at a Distance

Feet (Meters)	Center Beam	Beam Width	
	Foot-Candle (Lux)	Vertical 60°	Horizontal 90°
0.7' (0.2 m)	1.9 fc (21 lx)	0.8' (0.2 m)	1.3' (0.4 m)
1.3' (0.4 m)	0.5 fc (5.4 lx)	1.6' (0.5 m)	2.7' (0.8 m)
2.0' (0.6 m)	0.2 fc (2.2 lx)	2.4' (0.7 m)	4.0' (1.2 m)
2.7' (0.8 m)	0.1 fc (1.1 lx)	3.3' (1.0 m)	5.4' (1.7 m)
3.3' (1.0 m)	0.1 fc (1.1 lx)	4.1' (1.3 m)	6.7' (2.0 m)
4.0' (1.2 m)	0.1 fc (1.1 lx)	4.9' (1.5 m)	8.0' (2.4 m)




### Perfectly Level, Every Time

The LevelX system allows the composite sleeve to be up to  $\frac{3}{8}$ " (9.5 mm) out of level, in either direction, while still allowing the faceplate to be laser level.



The secret: The trim attaches to the adjustable reflector assembly—not the composite sleeve or body. Heavy foam gasket keeps light spill to a minimum.



Cree is a registered trademark of Cree Inc. MoistureBlock is a trademark of DSM&T Co. Inc.

© 2019 Hunter Industries Inc. Hunter, FX Luminaire, all related logos, and all other trademarks are property of Hunter Industries, registered in the U.S. and other countries.