FXLuminaire.

Incandescent Up Lights



Our premiere up light luminaire is built to last a lifetime but priced for the value-conscious project owner. Milled from solid billet brass, this is the best choice for applications that demand extreme durability and high performance. A wide range of filters and glare control devices allow the lighting designer to shape the beam for precise light painting of any fine exterior.


LO: Up Light



Years of Strength


For centuries, brass has been the material of choice for harsh outdoor environments. With its corrosion resistance and ability to incorporate fine mechanical details, solid brass is the perfect material for the most demanding lighting applications.

Note: This fixture is designed for up lighting only.



INCANDESCENT

ORDERING INFORMATION



FACTORY INSTALLED OPTIONS: Order 1 + 2 + 3

Step	Description	Code	
1	FIXTURE	LO	1000
2	LAMP	10, 20, 35, 50, NL	
3	FINISH	BS, NP	

EXAMPLE: LO-20W-BS = LO - 20W - Natural Brass Finish

FIELD INSTALLED OPTIONS: Order Individually

Glare Control	Lenses/Filters	Mounts	Mounts			
Hex Baffle (250015260000)	Frosted (250015170000)	Super Slot Spike (753900) 2" x 10" Included ▼				
RecessorRing (RRMR16)	Spread (250013550000)	Long Slot Spike (250015840000) 2.5" x 10"				
	Solite Spread (250015240000)	SuperJ-Box (<i>SJ-XX**</i>) 2.5" x 12"				
	Dichroic Peach (250015230000	Post Mount (<i>PM-XX**</i>) 2.5" x 13"				
	Dichroic Blue (250015200000)			m		
	Dichroic Green (250015210000)					
	Dichroic Red (250015220000)		V	Į		
	Light Blue (250015190000)					
	Light Green (250015180000)					
	1	Super Slot Spike	Long Slot Spike	Super J-Box XX**	Post Mount XX**	

EXAMPLE: 250015240000 = Solite Spread Lens

760.744.5240 | fxl.com

METALS



The LO includes choice of halogen MR-16 lamp, clear lens, metal finish, and a Super Slot Spike.

* May require longer lead time

** Denotes finish code



