FXLuminaire.

PROJECT
CATALOG #
ТҮРЕ
NOTES




ST-UV TRANSFORMER

30 W universal voltage step-down transformer

Quick Facts

- Universal input voltage: 85–305 VAC
- Output: 12 VAC
- 30 W capacity

- Screw terminal mounting
- Compact size





ST-UV SPECIFICATIONS

Output

_	
Power	30 W
Input Primary	85-305 VAC
Input Amperage Primary	0.75 A at 120 VAC, 0.5 A at 230 VAC
Output Voltage Secondary	12 VAC
Maximum Open Circuit Volts	12 VAC
Class	2

FX Luminaire

FX Luminaire is an industry-leading manufacturer of landscape and architectural lighting products. We focus on the advancement of LED technology and digital lighting control with zoning, dimming, and color adjustment capabilities. We offer a full spectrum of specificationdriven lighting fixtures that can be utilized to create elegant, cuttingedge landscape lighting systems for commercial or residential applications. Our products are available exclusively via our extensive professional distributor network.

I

94V-0 flame retardant plastic housing

Power

Materials

Input: 85-305 VAC Output: 12 VAC

Ambient Operating

Temperature -22°F to 158°F (-30°C to 70°C)

Weight 0.25 lbs. (0.1 kg)

Sustainability Innovation meets

conservation in the design and manufacturing of our products. Where we can, we use recycled materials while maintaining superior functionality. Our LED products provide highquality light at optimal energy efficency, lifespan, and durability.

Installation Requirements

Designed for installation on a vertical surface in the upright position only.

Warranty 10-year limited warranty

o-year iinnii





ST-UV ORDERING INFORMATION

Item

ST-UV

EXAMPLE TRANSFORMER CONFIGURATION: ST-UV

© 2020 Hunter Industries[™]. Hunter, FX Luminaire, all related logos, and all other trademarks are property of Hunter Industries, registered in the U.S. and other countries.