



PROJECT

CATALOG #

TYPE


NOTES

CP STANDARD PREMIUM

The CP wall light is engineered to bring light to walkways, stairways, and decks, as well as difficult areas that can not accommodate path lights or down lights.

Quick Facts

- Stamped copper construction
- Natural or powder coated finishes
- Silicone-encapsulated COB LED
- Tamper-resistant features
- Compatible with Luxor® technology
- Phase dimmable
- Input voltage: 10-15V



CP Wall Light SPECIFICATIONS

FX Luminaire

FX Luminaire is an industry-leading manufacturer of landscape and architectural lighting products with a focus on the advancement of LED technology and digital lighting control with zoning, dimming, and color adjustment capabilities. We offer a full spectrum of specification-driven lighting fixtures that can be utilized to create elegant, cutting-edge landscape lighting systems for commercial or residential applications. Our products are available exclusively via our extensive professional distributor network.

Materials

Stamped C110 copper faceplate, A380 aluminum housing, PBT construction box/sleeve, and stainless steel hardware.

Lamp

G4 lamp base. Preinstalled T3 LED lamp option with G4 base offers a warm 2,700K color temperature with a minimum rated life (L70) 33,000 hours.

Power

Input 10-15 VAC/VDC, 50/60 Hz. Remote transformer required (specify separately).

Socket

Socket contains MoistureBlock™ technology, preventing moisture from wicking up into sealed areas of the fixture.

Wiring

18 AWG (1 mm); SPT-1W; 202°F (105°C); 300V; 10' (3 m) length.

Housing

Die-cast aluminum housing with capacity for one G4 LED.

Faceplate

Stamped C110 copper faceplate with frosted polycarbonate lens.

Finish

Options of natural copper finish or TGIC powder coat finish.

Construction Sleeve

Vertical and horizontal ½" (13 mm) NPT knockouts. Sleeve protector included, preventing caving during wall fabrication.

Hardware

Tamper-resistant stainless steel fasteners included.

Ambient Operating Temperature

0°F to 140°F (-18°C to 60°C)

Weight

2.3 lbs. (1 kg)

IES Classification

Type IV

International Compliance

Compliant per IEC 60598-1 and IEC 60598-2-7 when used with International Wall Kit ("EKITWALL").

Control

Luxor zoning and dimming technology with use of Luxor Cube (LCM-LV). Luxor Technology allows up to 250 groups, dimmable in 1 increments between 0 and 100%.

Sustainability

Innovation meets conservation in the design and manufacturing of our products. Where we can, we use recycled materials while maintaining superior functionality. Our LED products provide high-quality light at optimal energy efficiency, lifespan, and durability.

Installation Requirements

Designed for recessed installation in a vertical wall in the down lighting position only.

Manufacturing

9001:2015 ISO certified facility

Warranty

10-year limited warranty on fixture.

Listings



CP Wall Light ORDERING INFORMATION

Fixture	Lamp	Finish	
CP*	LED20W 20W Equivalent LED Lamp, 2,700K	CU Natural Copper	FB Black
		BZ Bronze Metallic	WG White Gloss
		DG Desert Granite	FW Flat White
		WI Weathered Iron	AL Almond
		SB Sedona Brown	NP Nickel Plate

EXAMPLE FIXTURE CONFIGURATION:
 CP-LED20W-FB



*Includes sleeve with cover (250022040000)




ACCESSORY: Specify Separately

Accessories	Code
WALL LIGHT CONNECTION KIT  	EKITWALL

LUXOR TECHNOLOGY OPTIONS: Specify Separately



Cubes	Code
LOW-VOLTAGE CUBE Supports AC dimmable LEDs and incandescent MAX LOAD: 60W/5A	LCM-LV 
RELAY/0-10V CUBE Supports relay switch MAX LOAD: 250VAC/5A	LCM-RLY-010V 



Perfectly Level, Every Time

The LevelX system allows the composite sleeve to be up to 3/8" (9.5 mm) out of level, in either direction, while still allowing the faceplate to be laser level.

The secret: The trim attaches to the adjustable reflector assembly—not the composite sleeve or body. Heavy foam gasket keeps light spill to a minimum.



Cree is a registered trademark of Cree Inc. MoistureBlock is a trademark of DSM&T Co. Inc.

© 2019 Hunter Industries Inc. Hunter, FX Luminaire, all related logos, and all other trademarks are property of Hunter Industries, registered in the U.S. and other countries.