

INTERNATIONAL PRODUCT GUIDE

LANDSCAPE LIGHTING

FXLuminaire®



FINISHES

Metals								Powder coat – Standard					Powder coat – Specialty [†]				Composites	
AB Antique Bronze on Copper	AB Antique Bronze on Brass	AT Antique Tumbled on Copper	AT Antique Tumbled on Brass	CU Copper	BS Natural Brass	SS Stainless Steel	NP[‡] Nickel Plate	BZ Bronze Metallic	DG Desert Granite	WI Weathered Iron	SB Sedona Brown	FB Black	WG[‡] White Gloss	FW[‡] Flat White	AL[‡] Almond	SV[‡] Silver	CB Camo Bronze	DT Desert Tan

DESIGNER SERIES

Designer LED Up Lights ▼

◀ QZ

Height: 146 mm
Diameter: 45 mm
LEDs: 1
Finishes: BZ, DG, WI, SB, FB, WG[‡], FW[‡], AL[‡], SV[‡]
Material: Aluminium
CE Approved
 Accessory Required



◀ FB + colour

Height: 191 mm
Diameter: 51 mm
LEDs: 1, 3
Finishes: BZ, DG, WI, SB, FB, WG[‡], FW[‡], AL[‡], SV[‡]
Material: Aluminium
CE Approved
 Int'l Configuration Req'd



◀ NP + colour

Height: 213 mm
L Shroud: 269 mm
Diameter: 68 mm
LEDs: 3, 6, 9
Finishes: BZ, DG, WI, SB, FB, WG[‡], FW[‡], AL[‡], SV[‡]
Material: Aluminium
CE Approved
 Int'l Configuration Req'd

◀ QB

Height: 151 mm
Width: 75 mm
Depth: 55 mm
LEDs: 1
Finishes: BZ, DG, WI, SB, FB, WG[‡], FW[‡], AL[‡], SV[‡]
Material: Aluminium
CE Approved
 Accessory Required



◀ PB + colour

Height: 171 mm
Width: 102 mm
Depth: 57 mm
LEDs: 1, 3
Finishes: AB, AT, BS, NP[‡], BZ, DG, WI, SB, FB, WG[‡], FW[‡], AL[‡], SV[‡]
Material: Brass or Aluminium
CE Approved
 Int'l Configuration Req'd



◀ LC + colour

Height: 165 mm
Width: 114 mm
Depth: 76 mm
LEDs: 3, 6, 9
Finishes: AB, AT, BS, NP[‡], BZ, DG, WI, SB, FB, WG[‡], FW[‡], AL[‡], SV[‡]
Material: Brass or Aluminium
CE Approved
 Int'l Configuration Req'd

◀ FR + colour

Height: 170 mm
L Shroud: 200 mm
Diameter: 64 mm
LEDs: 1, 3
Finishes: CU, AB, AT, NP[‡]
Material: Copper/Brass
CE Approved
 Accessory Required



◀ NR + colour

Height: 170 mm
L Shroud: 200 mm
Diameter: 64 mm
LEDs: 3, 6, 9
Finishes: CU, AB, AT, NP[‡]
Material: Copper/Brass
CE Approved
 Accessory Required

◀ CC + colour

Height: 133 mm
L Shroud: 163 mm
Diameter: 41 mm
LEDs: 1, 3
Finishes: AB, AT, BS, NP[‡]
Material: Brass
CE Approved
 Accessory Required



◀ VS + colour

Height: 193 mm
L Shroud: 212 mm
Diameter: 64 mm
LEDs: 3, 6, 9
Finishes: AB, AT, BS, NP[‡]
Material: Brass
CE Approved
 Accessory Required

Designer LED Down Lights ▼

◀ QT

Height: 173 mm
Diameter: 53 mm
LEDs: 1
Finishes: BZ, DG, WI, SB, FB, WG[‡], FW[‡], AL[‡], SV[‡]
Material: Aluminium
CE Approved
 Accessory Required



◀ JB + colour

Height: 226 mm
Diameter: 59 mm
LEDs: 1, 3
Finishes: BZ, DG, WI, SB, FB, WG[‡], FW[‡], AL[‡], SV[‡]
Material: Aluminium
CE Approved
 Int'l Configuration Req'd



◀ DE + colour

Height: 246 mm
Diameter: 76 mm
LEDs: 3, 6, 9
Finishes: BZ, DG, WI, SB, FB, WG[‡], FW[‡], AL[‡], SV[‡]
Material: Aluminium
CE Approved
 Int'l Configuration Req'd

Designer LED Down Lights ▼



◀ LE

Height: 83 mm
Diameter: 41 mm
LEDs: 1
Finishes: AB, AT, BS, CU, NP[†], BZ, DG, WI, SB, FB, WG[†], FW[†], AL[†], SV[†]
Material: Aluminium or Copper/Brass
CE Approved
Int'l Configuration Req'd



◀ VE + colour

Height: 79 mm
Diameter: 59 mm
LEDs: 1, 3
Finishes: AB, AT, BS, CU, NP[†], BZ, DG, WI, SB, FB, WG[†], FW[†], AL[†], SV[†]
Material: Aluminium or Copper
CE Approved
Int'l Configuration Req'd



◀ NL + colour

Height: 84 mm
Width: 81 mm
LEDs: 1, 3, 6, 9
Finishes: AB, AT, BS, CU, NP[†], BZ, DG, WI, SB, FB, WG[†], FW[†], AL[†], SV[†]
Material: Brass or Aluminium
CE Approved
Custom Kit Required



◀ PS + colour

Height: 84 mm
Diameter: 81 mm
LEDs: 1, 3, 6, 9
Finishes: AB, AT, BS, NP[†], CU, BZ, DG, WI, SB, FB, WG[†], FW[†], AL[†], SV[†]
Material: Brass or Aluminium
CE Approved
Custom Kit Required

Designer LED Wall Lights ▼



◀ PO

Diameter: 38 mm
Height: 64 mm
LEDs: 1
Finishes: AB, AT, BS, NP[†], BZ, DG, WI, SB, FB, WG[†], FW[†], AL[†], SV[†]
Material: Brass
CE Approved
Accessory Required



◀ MO + colour

Diameter: 51 mm
Height: 83 mm
LEDs: 1, 3
Finishes: AB, AT, BS, NP[†], BZ, DG, WI, SB, FB, WG[†], FW[†], AL[†], SV[†]
Material: Brass
CE Approved
Accessory Required



◀ MS

Diameter: 94 mm
Depth: 51 mm
LEDs: 1
Finishes: AB, AT, BS, NP[†], BZ, DG, WI, SB, FB, WG[†], FW[†], AL[†], SV[†]
Material: Aluminium or Brass
CE Approved
Int'l Configuration Req'd



◀ CP/LM

CP Width: 127 mm
LM Width: 229 mm
Height: 89 mm
LEDs: 1 (CP); 2 (LM)
Finishes: AB, AT, CU, NP[†], BZ, DG, WI, SB, FB, WG[†], FW[†], AL[†], SV[†]
Material: Copper
CE Approved
Accessory Required



◀ UN/PD

UN Width: 127 mm
PD Width: 229 mm
Height: 89 mm
LEDs: 1 (UN); 2 (PD)
Finishes: AB, AT, BS, NP[†], BZ, DG, WI, SB, FB, CB, DT, WG[†], FW[†], AL[†], SV[†]
Material: Brass or Composite
CE Approved
Accessory Required

Designer LED Path/Area Lights ▼



◀ HC

Diameter: 92 mm
Height: 381 mm*
LEDs: 1
Finishes: AB, AT, CU, NP[†], BZ, DG, WI, SB, FB, WG[†], FW[†], AL[†], SV[†]
Material: Copper/Brass
Riser Required: P[†]
CE Approved
Accessory Required



◀ JS + colour

Diameter: 160 mm
Height: 419 cm*
LEDs: 1, 3
Finishes: AB, AT, CU, NP[†], BZ, DG, WI, SB, FB, WG[†], FW[†], AL[†], SV[†]
Material: Copper/Brass
Riser Required: G[†]
CE Approved
Accessory Required



◀ PF/DM + colour

PF Diameter: 127 mm
Riser Required: P[†]
DM Diameter: 180 mm
Riser Required: G[†]
Finishes: AB, AT, CU, NP[†], BZ, DG, WI, SB, FB, WG[†], FW[†], AL[†], SV[†]
LEDs: 1 (PF); 1, 3 (DM)
Material: Copper/Brass
CE Approved
Accessory Required



◀ SC/CA + colour

SC Diameter: 119 mm
Riser Required: P[†]
CA Diameter: 188 mm
Riser Required: G[†]
LEDs: 1 (SC); 1, 3 (CA)
Finishes: AB, AT, CU, NP[†], BZ, DG, WI, SB, FB, WG[†], FW[†], AL[†], SV[†]
Material: Copper/Brass
CE Approved
Accessory Required



◀ BD/CB + colour

BD Diameter: 119 mm
Riser Required: P[†]
CB Diameter: 188 mm
Riser Required: G[†]
LEDs: 1 (BD); 1, 3 (CB)
Finishes: AB, AT, CU, NP[†], BZ, DG, WI, SB, FB, WG[†], FW[†], AL[†], SV[†]
Material: Copper/Brass
CE Approved
Accessory Required



◀ PR/CV + colour

PR Diameter: 97 mm
Riser Required: P[†]
CV Diameter: 188 mm
Riser Required: G[†]
LEDs: 1 (PR); 1, 3 (CV)
Finishes: AB, AT, CU, NP[†], BZ, DG, WI, SB, FB, WG[†], FW[†], AL[†], SV[†]
Material: Copper/Brass
CE Approved
Accessory Required

* LED path lights are ordered in two parts: 1) Top Assembly and 2) Riser Assembly.
[†] Items in this finish are not returnable.

Designer LED Path/Area Lights ▾

◀ PL + colour



Height: 381 mm*
Diameter: 152 mm
LEDs: 1, 3
Finishes: BZ, DG, WI, SB, FB, WG[†], FW[†], AL[†], SV[†]
Material: Aluminium
Riser Required: A⁺
CE Approved
 Accessory Required

◀ TM + colour



Height: 381 mm*
Diameter: 127 mm
LEDs: 1, 3
Finishes: BZ, DG, WI, SB, FB, WG[†], FW[†], AL[†], SV[†]
Material: Aluminium
Riser Required: A⁺
CE Approved
 Accessory Required

◀ RW + colour



Height: 193 mm
Diameter: 103 mm
LEDs: 1, 3, 6, 9
Finishes: BZ, DG, WI, SB, FB, SV[†], WG[†], FW[†], AL[†], SV[†]
Material: Aluminium
CE Approved
 Accessory Required

◀ PM + colour



Height: 356 mm
XT Height: 470 mm
Diameter: 64 mm
LEDs: 1, 3, 6, 9
Finishes: BZ, DG, WI, SB, FB, SV[†], WG[†], FW[†], AL[†]
Material: Aluminium
CE Approved
 Int'l Configuration Req'd

◀ M-PL + colour



Height: 559 mm
Diameter: 127 mm
LEDs: 1
Finishes: BZ, DG, WI, SB, FB, WG[†], FW[†], AL[†], SV[†]
Material: Aluminium
CE Approved
 Int'l Configuration Req'd

◀ TD + colour



Height: 457 mm
XT Height: 749 mm
Diameter: 127 mm
LEDs: 1, 3, 6, 9
Finishes: AB, AT, CU, NP[†], BZ, DG, WI, SB, FB, WG[†], FW[†], AL[†], SV[†]
Material: Copper/Brass
CE Approved
 Accessory Required

◀ FG + colour



Height: 559 mm
Diameter: 127 mm
LEDs: 1, 3, 6, 9
Finishes: AB, AT, CU, NP[†], BZ, DG, WI, SB, FB, WG[†], FW[†], AL[†], SV[†]
Material: Copper/Brass
CE Approved
 Accessory Required

Designer LED Underwater Light ▾

◀ LP + colour



Stand Included

Diameter: 69 mm
Height: 48 mm
LEDs: 1, 3
Finish: BS
Lead: 9 m or 30 m
Material: Brass
CE Approved
 Int'l Configuration Req'd

◀ LL + colour



Length: 163 mm
Diameter: 84 mm
Height: 134 mm
LEDs: 1, 3, 6, 9
Finish: BS
Lead: 9 m or 30 m
Material: Brass
CE Approved
 Int'l Configuration Req'd

Designer LED In-Grade & Well Lights ▾

◀ FC + colour



Ring (RG)

Cowling (CW)

Ground Wash (GW)

Louvre (LV)

Height: LV: 130 mm
 RG: 122 mm
 CW: 173 mm
 GW: 145 mm
Diameter: 102 mm
LEDs: 1, 3, 6, 9
Finish: AB, AT, BS, NP[†], BZ, DG, WI, SB, FB, WG[†], FW[†], AL[†], SV[†]
Material: Brass
CE Approved
 Int'l Configuration Req'd

◀ PE + colour



Height: 193 mm
Diameter: 103 mm
LEDs: 3, 6, 9
Finish: CB
Material: Composite
CE Approved
 Int'l Configuration Req'd

◀ KG + colour



Diameter: 152 mm
Height: 234 mm
LEDs: 3, 6, 9
Finishes: AB, AT, BS, NP[†], BZ, DG, WI, SB, FB, WG[†], FW[†], AL[†]
Material: Brass or Aluminium
CE Approved
 Int'l Configuration Req'd

STANDARD SERIES

Standard Up Lights ▼



◀ RS

Height: 165 mm
L Shroud: 199 mm
Diameter: 61 mm
Lamp Base: MR-16
Finishes: BZ, DG, WI, SB, FB, WG[†], FW[†], AL[‡], SV[‡]
Material: Zinc
CE Approved
Accessory Required



◀ MU

Height: 191 mm
L Shroud: 221 mm
Diameter: 61 mm
Lamp Base: MR-16
Finishes: BZ, DG, WI, SB, FB, WG[†], FW[†], AL[‡], SV[‡]
Material: Aluminium
CE Approved
Int'l Configuration Req'd



◀ LR

Height: 153 mm
L Shroud: 191 mm
Diameter: 61 mm
Lamp Base: MR-16
Finishes: CU, NP[†]
Material: Copper/Brass
CE Approved
Accessory Required



◀ LO

Height: 153 mm
Diameter: 57 mm
Lamp Base: MR-16
Finishes: BS, NP[†]
Material: Brass
CE Approved
Accessory Required

Standard Path/Area Lights ▼

◀ SP(-A)

Height: 394 mm*
Diameter: 92 mm
Lamp Base: G4
Finishes: AB, AT, CU, NP[†], BZ, DG, WI, SB, FB, WG[†], FW[†], AL[‡], SV[‡]
Material: Copper/Brass or Aluminium
CE Approved
Accessory Required



◀ DL(-A)

Height: 381 mm*
Diameter: 159 mm
Lamp Base: G4
Finishes: AB, AT, CU, NP[†], BZ, DG, WI, SB, FB, WG[†], FW[†], AL[‡], SV[‡]
Material: Copper/Brass or Aluminium
CE Approved
Accessory Required



◀ PF/DM(-A)

PF Diameter: 102 mm
DM(-A) Diameter: 180 mm
Lamp Base: G4
Finishes: CU, NP[†], BZ, DG, WI, SB, FB, WG[†], FW[†], AL[‡], SV[‡]
Material: Copper/Brass or Aluminium
CE Approved
Accessory Required



◀ SC/CA(-A)

SC Diameter: 119 mm
CA(-A) Diameter: 188 mm
Lamp Base: G4
Finishes: CU, NP[†], BZ, DG, WI, SB, FB, WG[†], FW[†], AL[‡], SV[‡]
Material: Copper/Brass or Aluminium
CE Approved
Accessory Required



◀ BD/CB

BD Diameter: 119 mm
CB Diameter: 188 mm
Lamp Base: G4
Finishes: CU, NP[†], BZ, DG, WI, SB, FB, WG[†], FW[†], AL[‡], SV[‡]
Material: Copper/Brass
CE Approved
Accessory Required



◀ PR/CV

PR Diameter: 97 mm
CV Diameter: 180 mm
Lamp Base: G4
Finishes: CU, NP[†], BZ, DG, WI, SB, FB, WG[†], FW[†], AL[‡], SV[‡]
Material: Copper/Brass
CE Approved
Accessory Required



◀ AP/AN

AP Diameter: 99 mm
AN Diameter: 160 mm
Lamp Base: G4
Finishes: CU, NP[†], BZ, DG, WI, SB, FB, WG[†], FW[†], AL[‡], SV[‡]
Material: Copper/Brass
CE Approved
Accessory Required



◀ DP

Height: 343 mm*
Diameter: 74 mm
Lamp Base: G4
Finishes: CU, NP[†], BZ, DG, WI, SB, FB, WG[†], FW[†], AL[‡]
Material: Copper/Brass
CE Approved
Accessory Required



◀ GN

Height: 572 mm
 (with 457 mm riser)
Diameter: 254 mm
Riser Diameter: 31.75 mm
Lamp Base: G4
Finishes: CU, NP[†], BZ, DG, WI, SB, FB, WG[†], FW[†], AL[‡]
Material: Copper/Brass
CE Approved
Accessory Required



◀ TM

Height: 381 mm*
Diameter: 127 mm
Lamp Base: G4
Finishes: BZ, DG, WI, SB, FB, WG[†], FW[†], AL[‡], SV[‡]
Material: Aluminium
CE Approved
Accessory Required



◀ PL

Height: 381 mm*
Diameter: 152 mm
Lamp Base: G4
Finishes: BZ, DG, WI, SB, FB, WG[†], FW[†], AL[‡], SV[‡]
Material: Aluminium
CE Approved
Accessory Required



*Items in this finish are not returnable.

Standard Wall Lights ▼

◀ UN/PD



UN Face Width: 127 mm
PD Face Width: 229 mm
Face Height: 89 mm
Lamp: G4 Xenon or Halogen
Finishes: BS, NP[†], BZ, DG, WI, SB, FB, CB, DT, WG[†], FW[†], AL[†], SV[†]
Material: Brass or Composite
CE Approved
Accessory Required

◀ CP/LM



CP Face Width: 127 mm
LM Face Width: 229 mm
Face Height: 89 mm
Lamp: G4 Xenon or Halogen
Finishes: CU, NP[†], BZ, DG, WI, SB, FB, WG[†], FW[†], AL[†], SV[†]
Material: Copper
CE Approved
Accessory Required

Standard Down Lights ▼

◀ MD



Length: 241 mm
Diameter: 66 mm
Lamp: Halogen MR-16
Finishes: BZ, DG, WI, SB, FB, WG[†], FW[†], AL[†], SV[†]
Material: Aluminium
CE Approved
Int'l Configuration Req'd

Standard In-Grade/Well Lights ▼

◀ LB



Length: 163 mm
Diameter: 84 mm
Base Width: 137 mm
Lamp: MR-16
CE Approved
Int'l Configuration Req'd

Ring (RG) Cowling (CW)



◀ FC

Height:
 LV: 130 mm
 RG: 122 mm
 CW: 173 mm
Diameter: 102 mm
Lamp: Halogen MR-11
Finishes: BS, NP[†], CB, DT
Material: Brass or Composite
CE Approved
Int'l Configuration Req'd

Ring (RG) Cowling (CW)



◀ RP

Height:
 LV: 236 mm
 RG: 229 mm
 CW: 279 mm
Diameter: 171 mm
Lamp: Halogen MR-16
Finishes: BS, NP[†], CB, DT
Material: Brass or Composite
CE Approved
Int'l Configuration Req'd

◀ TE



Height: 311 mm
Diameter: 163 mm
Lamp: Halogen MR-16
Finishes: BS, NP[†]
Material: Brass
CE Approved
Int'l Configuration Req'd

CONTROLLERS & ACCESSORIES

Luxor Controller ▼

◀ LUXOR

Height: 330 mm
Width: 203 mm
Depth: 127 mm
Watts: 150, 300
Finishes: SS, M
Input: 230V



◀ LUXOR SATELLITE

Height: 330 mm
Width: 203 mm
Depth: 127 mm
Watts: 300
Finishes: SS, M

Luxor Accessories ▼

◀ LAM

Light Assignment Module for use with Luxor Wi-Fi technology



◀ APP COMMUNICATION

Wi-Fi module with antenna

Retrofit Lamps ▼

◀ MR-16 LED LAMPS

Base: GU5.3
Beam Angles: 4
Max Lumens: 260-370 lm



◀ G4 LAMPS

Base: T3
Max Lumens: 76-123 lm



Mounting Accessories ▼

◀ RISERS AND COUPLINGS

Couplings and risers offer installation flexibility and customisation for at-grade or wall-mounted applications.



◀ MOUNTS

Use mounts and junction boxes for a clean look and installation.

◀ TB-XX

Dual input junction box for up or down lights with strain relief. Custom anchor bolts included.



◀ GM-XX

IP67 ground mount for up lights with conduit installation.



◀ EKITSPIKE

Junction box stake for up lights with strain relief and wire connectors included.



◀ EKITWALL

Wire connector and strain relief for recessed wall lights.

FXLuminaire

A Hunter Industries Company

Our mission is to create the most energy-efficient lighting products in the world while maintaining the highest level of quality and reliability. In every instance we will back our innovations with the unwavering support our customers need to succeed.



Gregory R. Hunter, CEO of Hunter Industries



Gene Smith, President, Landscape Irrigation and Outdoor Lighting

Website fxl.com | Customer Support +1 760-744-5240 | Technical Service +1 760-591-7383

USA HEADQUARTERS

1940 Diamond Street
San Marcos, California 92078, USA
TEL: +1 760-744-5240

MEXICO

ISO 9001:2015 Certified
Calle Nordika #8615
Parque Industrial Nordika
Tijuana, B.C., Mexico CP 22640
TEL: +52 664-903-1300

EUROPE

Avda. Diagonal 523, 5^a- 2^o
Edificio Atalaya
08029 Barcelona, Spain
TEL: +34 934-948-881

AUSTRALIA

Suite 7, 202 Ferntree Gully Road
Notting Hill, Melbourne
Victoria 3168, Australia
TEL: +61 3-9562-9918
FAX: +61 3-9558-6983

MIDDLE EAST

P.O. Box 2370
Amman, 11941, Jordan
TEL: +962 6-5152882
FAX: +962 6-5152992

CHINA

B1618, Huibin Office Bldg.
No. 8, Beichen Dong Street
Beijing 100101, China
TEL/FAX: +86 10-84975146

This brochure was printed on Forest Stewardship Council® (FSC) certified paper with soy inks. The FSC is an international organization established to promote the responsible management of the world's forests.

© 2018 Hunter Industries Incorporated  Please recycle.

FXLIT-177-PG-EM 10/18



Printed using
100% Wind
Energy, (RECs)