


## DETAIL LEGEND:

- ① FX LUMINAIRE "LP-VR" FIXTURE PER PLAN
- ② 2.0" [51 mm] SCHEDULE 40 PCV OR CORE DRILL TO FIXTURE DIMENSIONS
- ③ BOTTOM OF WATER FEATURE
- ④ WATER LEVEL WITHIN FEATURE
- ⑤ ELECTRICAL CONDUIT WITH SWEEP ELLS, AS REQUIRED
- ⑥ DIRECT BURY, UF/UL, COPPER, LOW VOLTAGE CABLE WITH UL 486D (IEC/EN 60998) RATED WATERPROOF CONNECTION. LEAVE MINIMUM WIRE LOOP COILED FOR FUTURE SERVICE ABOVE WATER LEVEL.
- ⑦ HEAT SHRINK WIRE CONNECTORS

## NOTES

- A. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- B. ACCEPTS 10-15 VOLTS - AC OR DC
- C. SEE PLAN LEGEND FOR LED BOARD OPTION, BEAM SPREADS, AND ACCESSORIES.
- D. ALWAYS REFER TO FX PRODUCT INSTALLATION NOTES PRIOR TO INSTALLATION.



# LED UNDERWATER LIGHT (LP-VR)

**FXLuminaire.** SP.LP.02

NOT TO SCALE  
REV: 2022-01-31