



DETAIL LEGEND:

- ① FX LUMINAIRE "LP-HZ" FIXTURE PER PLAN
- ② SUPPORT STAND
- ③ BOTTOM OF WATER FEATURE
- ④ WATER LEVEL WITHIN FEATURE
- ⑤ ELECTRICAL CONDUIT WITH SWEEP ELLS, AS REQUIRED
- ⑥ DIRECT BURY, UF/UL, COPPER, LOW VOLTAGE CABLE WITH UL 486D (IEC/EN 60998) RATED WATERPROOF CONNECTION. LEAVE MINIMUM WIRE LOOP COILED FOR FUTURE SERVICE ABOVE WATER LEVEL.
- ⑦ HEAT SHRINK WIRE CONNECTORS

NOTES

- A. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- B. ACCEPTS 10-15 VOLTS - AC OR DC
- C. SEE PLAN LEGEND FOR LED BOARD OPTION, BEAM SPREADS, AND ACCESSORIES.
- D. ALWAYS REFER TO FX PRODUCT INSTALLATION NOTES PRIOR TO INSTALLATION.



LED UNDERWATER LIGHT (LP-HZ)

FXLuminaire. SP.LP.01

NOT TO SCALE

REV: 2022-01-31